

◀ **SPIDownload** HSPIDownload RFConfig GPIOConfig MultiDo ▶

<input checked="" type="checkbox"/>	E:\BeeHive\bootloader_dio_40m.bin	...	@	0x1000
<input checked="" type="checkbox"/>	E:\BeeHive\partitions.bin	...	@	0x8000
<input checked="" type="checkbox"/>	E:\BeeHive\boot_app0.bin	...	@	0xc000
<input checked="" type="checkbox"/>	E:\BeeHive\firmware.bin	...	@	0x10000
<input checked="" type="checkbox"/>	E:\BeeHive\spiffs.bin	...	@	0x3b1000
<input type="checkbox"/>		...	@	
<input type="checkbox"/>		...	@	
<input type="checkbox"/>		...	@	

SpiFlashConfig

CrystalFreq :

40M ▾

CombineBin

Default

SPI SPEED

SPI MODE

☒ 40MHz☐ 26.7MHz☐ 20MHz☐ 80MHz☐ QIO☒ QOUT☐ DIO☐ DOUT☐ FASTRD

FLASH SIZE

☐ 8Mbit☐ 16Mbit☒ 32Mbit☐ 64Mbit☐ 128Mbit☐ SpiAutoSet☐ DoNotChgBin☐ LOCK SETTINGS

DETECTED INFO

flash vendor:

EFh : WB

flash devID:

4016h

QUAD;32Mbit

crystal:

40 Mhz

Download Panel 1

Download

下载中...

AP: 3C71BF034751 STA: 3C71BF034750
 BT: 3C71BF034752 ETHERNET: 3C71BF034753

START

STOP

ERASE

COM:

COM9 ▾

BAUD:

460800 ▾